

600 lt



530 x 530

model	doors	grilles included in supply	temperature	refrigerating gas	absorbed power	voltage	net weight	gross weight	dimensions	packing	price
cod.	n.	n.	°C	cod.	Watt	Volt/Hz	kg	kg	W mm D mm H mm	W mm D mm H mm	€
PPCC060TN		3	0 / +10	R134a	410	230-1 50/60Hz	108	120	720 715 2080	750 760 2240	2.015,00
PPCC060T2		3	-2 / +10	R134a	410	230-1 50/60Hz	109	121	720 715 2080	750 760 2240	2.120,00
PPCC060BT		3	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	112	124	720 715 2080	750 760 2240	2.525,00
PPCC060TN2P		4	0 / +10	R134a	410	230-1 50/60Hz	113	125	720 715 2080	750 760 2240	2.360,00
PPCC060T22P		4	-2 / +10	R134a	410	230-1 50/60Hz	114	126	720 715 2080	750 760 2240	2.410,00
PPCC060BT2P		4	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	117	129	720 715 2080	750 760 2240	2.770,00
PPCC060TNGL		3	0 / +10	R134a	410	230-1 50/60Hz	118	130	720 725 2080	750 760 2240	2.365,00
PPCC060T2GL		3	-2 / +10	R134a	410	230-1 50/60Hz	118	130	720 725 2080	750 760 2240	2.440,00
PPCC060BTGL		3	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	130	142	720 725 2080	750 760 2240	2.975,00

remote unit / predisposto per motore remoto / **ohne Aggregat** / sans groupe logé / predispuesto para motor remoto

PPCC060TNMR		3	0 / +10	R134a	30	230-1 50/60Hz	95	107	720 715 2080	750 760 2240	1.900,00
PPCC060BTMR		3	-18 / -22	R507 (R404a)	30	2230-1 50/60Hz	96	108	720 715 2080	750 760 2240	2.005,00
PPCC060TNMR2P		4	0 / +10	R134a	30	230-1 50/60Hz	100	112	720 715 2080	750 760 2240	2.105,00
PPCC060BTMR2P		4	-18 / -22	R507 (R404a)	30	230-1 50/60Hz	101	113	720 715 2080	750 760 2240	2.210,00
PPCC060TNMRGL		3	0 / +10	R134a	30	230-1 50/60Hz	105	117	720 725 2080	750 760 2240	2.190,00
PPCC060BTMRGL		3	-18 / -22	R507 (R404a)	30	230-1 50/60Hz	110	122	720 725 2080	750 760 2240	2.430,00

700 lt



GN 2/1 650 x 530

model	doors	grilles included in supply	temperature	refrigerating gas	absorbed power	voltage	net weight	gross weight	dimensions	packing	price
cod.	n.	n.	°C	cod.	Watt	Volt/Hz	kg	kg	W mm D mm H mm	W mm D mm H mm	€
PPCC070TN		3	0 / +10	R134a	410	230-1 50/60Hz	111	125	720 815 2080	750 860 2240	2.065,00
PPCC070T2		3	-2 / +10	R134a	410	230-1 50/60Hz	112	126	720 815 2080	750 860 2240	2.175,00
PPCC070BT		3	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	115	129	720 815 2080	750 860 2240	2.575,00
PPCC070TN2P		4	0 / +10	R134a	410	230-1 50/60Hz	116	130	720 815 2080	750 860 2240	2.410,00
PPCC070T22P		4	-2 / +10	R134a	410	230-1 50/60Hz	117	131	720 815 2080	750 860 2240	2.460,00
PPCC070BT2P		4	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	120	134	720 815 2080	750 860 2240	2.825,00
PPCC070TNGL		3	0 / +10	R134a	410	230-1 50/60Hz	121	135	720 825 2080	750 860 2240	2.420,00
PPCC070T2GL		3	-2 / +10	R134a	410	230-1 50/60Hz	121	135	720 825 2080	750 860 2240	2.495,00
PPCC070BTGL		3	-18 / -22	R507 (R404a)	580	230-1 50Hz 230-1 60Hz	133	147	720 825 2080	750 860 2240	3.025,00

remote unit / predisposto per motore remoto / **ohne Aggregat** / sans groupe logé / predispuesto para motor remoto

PPCC070TNMR		3	0 / +10	R134a	30	230-1 50/60Hz	98	112	720 815 2080	750 860 2240	1.955,00
PPCC070BTMR		3	-18 / -22	R507 (R404a)	30	230-1 50/60Hz	99	113	720 815 2080	750 860 2240	2.065,00
PPCC070TNMR2P		4	0 / +10	R134a	30	230-1 50/60Hz	103	117	720 815 2080	750 860 2240	2.160,00
PPCC070BTMR2P		4	-18 / -22	R507 (R404a)	30	230-1 50/60Hz	104	118	720 815 2080	750 860 2240	2.265,00
PPCC070TNMRGL		3	0 / +10	R134a	30	230-1 50/60Hz	108	122	720 825 2080	750 860 2240	2.245,00
PPCC070BTMRGL		3	-18 / -22	R507 (R404a)	30	230-1 50/60Hz	113	127	720 825 2080	750 860 2240	2.485,00