

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	PASTA COOKER	ELECTRIC	NEDE72128

DESCRIPTION

ELECTRIC PASTA COOKER 1 WELL 28 LT.



TECHNICAL DATA:

STRUCTURE	FLOOR	WELL CAPACITY	28 LT.
WIDTH	400 mm	WELL DIMENSIONS	305x340x285 mm
DEPHT	730 mm		
HEIGHT	900 mm		
NET WEIGHT	43.5 kg		
VOLUME	0.26 m3		
ELECTRIC POWER	5.7 kW		
PHASE	3N		
FREQUENCY	50/60 Hz		
VOLTAGE	400 V		

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	PASTA COOKER	ELECTRIC	NEDE72128

FEATURES:

Electric Pasta-cooker, single well, Monoblock unit on cupboard with hinged door. Cook top made of stainless steel AISI 304, thickness 15/10, pre-fitted for head-to head connection. Pressed top with spillage basin and wide foam expansion area. Pressed stainless steel well (AISI 316), polished with radiused corners for easy cleaning. Water is loaded via electric valve activated by using the switch on the control panel. Fast filling and top-up options. Pressure switch prevents heating if well is empty. Fixed water tap in stainless steel located in the back part over the draining board. Heating by means of shielded electrical resistances positioned inside the well to improve output, the tilting mechanism makes well cleaning easier. Heating controlled by means of power regulator in order to make the boiling process more efficient. Equipped with manually resettable safety thermostat. 28 lt.- well capacity. Dimensions of the well in cm. 30.5x34x28.5h. Water drainage via tap inside the base unit can be activated in the front part. Height-adjustable feet in stainless steel. **SUPPLIED WITHOUT BASKETS AND LID.**


STANDARD ACCESSORIES:

OPTIONAL ACCESSORIES:

• LID FOR PASTA COOKER	SXPCC7
• BASKET 1/3 FOR PASTA COOKER - 600 mm MODULE ONLY	SXPCF13
• BASKET 1/3 FOR PASTA COOKER - SIDE HANDLES	SXPCL13
• KIT 2 BASKETS 1/3 FOR PASTA COOKER - COMPLETE WITH FRAME	SXPCKF913
• BASKET 2/3 PASTA COOKER WITH LATERAL SUPPORT	SXPCC23
• KIT OF 3 SINGLE SERVING BASKETS INCL. FRAME FOR 28 AND 42 LT WELL	SXPC3MP

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	PASTA COOKER	ELECTRIC	NEDE72128

INSTALLATION SCHEME



 E1	SOCKET	400 V	3N
 AF	COLD WATER	Ø 3/4"	100 mm
 AC	HOT WATER		
 G	GAS		
 S	DRAINING	Ø 1"	0 mm

NOTES FOR THE INSTALLER:

All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.

Gas connections must not use welded tubes.

Gas connections must be jacketed according to current rules in the country.

Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter length (except where otherwise required in the drawing).

All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.

The specification shown in this document are to be considered not bounding.

The company reserves the right to make technical changes at any moment.