

**4 ELECTRIC PLATES RANGE ON CABINET-
400V**

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Watertight fully sealed cast iron plates, fitted with thermal protection devices. Each plate is controlled by a 5-position switch. Open lower compartment.



Power supply	Electricity	Product fitting up	with integrated undercompartment
--------------	-------------	--------------------	----------------------------------

Worktop thickness	2 mm
-------------------	------

Functional features

- Nr. 4 cast iron square electric cooking plates, dimensions 29.5x29.5 cm.
- Each plate power rated at 4 kW; adjustable heating on 4 working-positions.
- Open lower compartment.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam, on multi-elements support.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Worktop with pressed recess for collection of juices and for cooking plate housing.
- Insulation beneath the cooking surface to reduce surface temperatures on the front and to improve user comfort.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Sealed flue on the top.
- Access to all components through front compartment and control console.
- Maintenance of inner components does not require appliance displacement.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).

Safety equipment and approvals

- Safety thermostat, integrated to the plates, against overheating due to idling.
- Approval to European Standard EN 1672-2 Hygienic Design.
- CE approvals in respect of all directives and regulations.
- IPX5 protection rating.

Optionals and Accessories

- The lower compartment can be fitted with doors and container rack.

Technical Data

Working voltage	400V 3N ~ 50 ÷ 60 Hz	Electric Power	16 kW
Dimensions	80x92x90 cm	Packing	86x102x131 cm

4 ELECTRIC PLATES RANGE ON CABINET- 400V
Icon9000 prof.900 - 2 mm

