

ELECTRIC FRYER 2 WELLS 21+21 L

Fryer made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed wells, sealed into top, generously coved with large drain zone; each well delivered with 2 baskets and 1 lid. Mechanical controls. Temperature control through thermostat 100-185°C. Tilting heating elements in the well. Pre-setting for remote control of power peaks.



Control panel	mechanical	Energy Control	Pre-Setting for remote control of power peaks
Liter each well	21	Power supply	Electricity
Productivity	68 kg/h french fries (AGA)	Well quantity	2
Worktop thickness	2 mm		

Functional features

- Electric fryer 2 wells made in AISI 304 stainless steel - capacity 21 + 21 lt
- Large recess in the upper section for oil expansion with the same capacity of the well.
- Heating by electrical heating elements fitted inside the well, which can be tipped vertically for easy cleaning.
- Fried potatoes productivity (base on AGA standards): 34 kg/h per well.
- Heat exchange surface area calculated for specific output of no more than 5 watt/cm² for a longer oil life.
- Temperature control through thermostat with diathermic oil (+ sensitive).
- Optimal functionality and easy cleaning due to absence of fixed back basket hanger.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam, on multi-elements support.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Oil drain pipe fixed to well, with ball-valve tap fitted with heat-resistant handle.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Sealed flue on the top.
- Hinged doors, with sandwich panel, made in AISI 304 stainless steel, grip directly pressed on the door plate, easy to clean.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Lower compartment with two doors.
- Hinged doors, with sandwich panel, made in AISI 304 stainless steel, grip directly pressed on the door plate, easy to clean.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).

Safety equipment and approvals

- Safety thermostat
- Safety cut off when the electric elements are in the vertical position.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- IPX5 protection rating.

Standard equipment

- n.2 baskets each well, made in chromium-plated steel, dimensions 15x36.8x12 cm
- Well lid in AISI 304 stainless steel full covering of the well, it can be fitted under the fryer.
- Chromium-plated steel bottom mesh with basket support outside the well.
- Oil drainage line extension located inside the door, for safe and easy oil drainage of oil, even when hot, away from the fryer itself.



1N1FR2E



Optionals and Accessories

- Single basket in chromed steel.

Technical Data

<i>Working voltage</i>	400V 3N ~ 50 ÷ 60 Hz	<i>Net Weight</i>	110 kg
<i>Gross Weight</i>	120 kg	<i>Electric Power</i>	36 kW
<i>Dimensions</i>	80x92x90 cm	<i>Packing</i>	86x102x131 cm

Icon9000 prof.900 - 2 mm
ELECTRIC FRYER 2 WELLS 21+21 L



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

01/07/2024